

MAXIMUM INDICATING GAUGES

2½" Stainless Case or 4½" Cast Aluminum Case

P2598LZSS-M

CASE: 300 series stainless steel.
RING: 300 series stainless steel, bayonet type with gasket.
LENS: Acrylic.
DIAL: Aluminum, white finished with black markings.
POINTER: Aluminum, black non-adjustable pointer
MAX POINTER: Aluminum, red adjustable
MOVEMENT: Stainless steel.
TUBE & SOCKET: 316 Stainless steel.
CONNECTION: 1/4" NPT bottom outlet.
ACCURACY: ±1.6% Full Scale
(exceeds ASME B40.100 Grade B).
PROCESS TEMPERATURE: -40 to 250°F (-40 to 120°C).
AMBIENT TEMPERATURE: -40 to 140°F (-40 to 60°C).



See Page 16 for further product specifications.

P4509LX-M

CASE: Black cast-aluminum with a 3-hole surface-mount rear flange.
RING: Stainless steel.
LENS: Polycarbonate.
DIAL: Aluminum, white finished with black markings.
POINTER: Aluminum, black, micro-adjustable.
MAX POINTER: Aluminum, red adjustable
MOVEMENT: Stainless steel rotary type.
TUBE & SOCKET: Phosphor-bronze tube, brass socket.
CONNECTION: 1/4" NPT brass, bottom outlet.
ACCURACY: ±1/2% Full Scale (ASME B40.100 Grade 2A).
PROCESS TEMPERATURE: -40 to 200°F (-40 to 93°C).
AMBIENT TEMPERATURE: -40 to 140°F (-40 to 60°C).



See Page 3 for further product specifications.

